



Hersteller

B.E.G. LUXOMAT



92731



PD11-DALI-SYS-FLAT

Product group

DALI-SYS

Model / Variant / Configuration

Number / Name



Product without accessories

Dimensions



0mm/0mm



Low profile DALI multisensor (visible height: 0,85 mm)
Powered via DALI bus
Seamless integration in B.E.G. LUXOMATnet DALI-SYS
Detection area can be extended thanks to master-slave-mode
Semi-automatic, full-automatic or twilight switch mode
Integrated daylight harvesting circuit (or switch output)
Guided Light, Soft-Start PLUS, Orientation light PLUS
Works out-of-the box for easy installation check
Full range of functions can only be activated with other products of the

product group B.E.G. LUXOMATnet
DALI-SYS
Spring clips for quick and easy
installation in suspended ceilings
Includes blinds and clamp ring for
installation into light fittings
Flush mounting with accessory 92833,
surface mounting with accessories 92833
and 92121
underground car parks, entrance halls,
corridors/hallways, staircases, small
offices, open-plan offices, conference
rooms

Voltage: via DALI Bus, max. 22.5 V DC

Dimensions: Ø 52 x 48 mm

Settings: B.E.G. PC Tools, B.E.G.
DALI-SYS router

typ. power input: 7 mA

Detection area: horizontal 360°
(Ceiling mounting)

Range: max. Ø 9 m across max. Ø 6 m
towards max. Ø 3 m seated

Monitored area (tangential movement):
63 m² / 2.5 m mounting height

Mounting height min./max./recommended:
2 m / 5 m / 2.5 m

Degree / class of protection: IP20 /
Class II

Ambient temperature: -25 °C to +50 °C

Housing: polycarbonate, UV-resistant

Follow-up time: 1 sec – 120 min

Orientation light: 5 – 100 % / 1 min
– 120 min / ?

Brightness set value: 10 – 2500 Lux