


Luminaires

Hersteller	Regent
Article number	2004.6960
Product name	TWEAK2 S2U1950 LED11600-830 WH IF2CSEDI EU
Product group	Freestanding luminaire
Mounting type	Freestanding
Mounting place	Floor
Test mark	

Model / Variant / Configuration

Number / Name	---
---------------	-----

Description

Product without accessories

Luminaires

Absolute Photometry	
LiTG class	D53
CIE flux codes	59 88 97 27 100
Protection class	Protection class I
Protection degree	IP 20

Dimensions

Diameter/Height	0mm/0mm
-----------------	---------

Description

Freestanding luminaire Tweak Office twin head, with LED, system power: 84 W, standby power 1 W, luminous flux of luminaire 11600 lm, colour rendering index CRI > 80, colour temperature 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, office-compatible and glare-free according to EN 12464-1 ($UGR < 19$; $L_{max} \geq 65^\circ \leq 3000 \text{ cd/m}^2$), photobiological safety: the luminaire poses no danger (RG0), 230 V, direct-indirect light emission, 27%/73%, independently dimmable and switchable, with control element (2-channel) on the rod, luminaire head 2x90°adjustable, one-piece housing in die-cast aluminium, white, RAL 9016, thermo painted, office-suitable microprismatic CLD optics (Controlled Luminance Diffusor) for perfect glare control, 2 integral control gears, SensoDim®, with light/movement sensor, base plate, U-shaped, 3m power supply cable with IEC 7/7 european plug, Regent certified MINERGIE®-Modul luminaires S.A.F.E. 2019 (Re-0309), luminaire complies with the strict requirements for Minergie-certified luminaires protection class I, ingress protection IP20, glow wire test 650 °C, this product contains a light source of energy efficiency class A and EPREL registration number: 1140597L = 651 mm, B = 535 mm, total height = 1950 mm