



### Luminaire

Hersteller	lightnet
No d'article	QAXCWE-830E-CE-R100-L785
Nom du produit	Liquid Line-AX
Product group	Ceiling Surface Mounted luminaire
Mode de montage	Construction
Lieu de montage	Plafond
Unité de contrôle	EVG
Marquage	CE

### Model / Variant / Configuration

Nombre / Nom	---
--------------	-----

### Description

Basic Ambient Semi-Recessed - M6

### Dimensions

Diamètre/Hauteur	0mm/0mm
------------------	---------

## Description

LED surface mounted light system. Direct only light distribution. Highly flexible system consisting of linear elements, vertically and horizontally curved elements and Y- and X-connectors. Each module is designed as a stand-alone luminaire with an integrated driver and can be connected to the other modules using a sophisticated connector system to create any desired lighting structure.

Millimeter-precise length production as well as special bends (Opal only) possible. Based on customer specification, Lightnet creates technical drawings of the desired structure for review and approval.

Luminaire body with smooth bends made of 40mm wide aluminium profile, crafted in one piece with no visible seams at the ends. Surface white, silver, graphite, black, champagne or copper coated. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Precision lenses with louvre for wide uniform symmetrical light distribution with high glare limitation ( $UGR < 19$ ). Louvre available in various surfaces. Satin opal diffuser for general lighting with maximum transmittance and homogeneous lighting. Driver optionally switchable or dimmable (DALI, Touch-Dim, Casambi). Colour temperature 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning  $\leq$  MacAdam 3. Colour rendering  $CRI > 80$ ,  $CRI > 90$  or Full Spectrum.